EVERGLOW STAIR NOSINGS & TREADS

Cleaning Instructions

EverGlow Stair Nosings and Renovation Stair Treads are durable and long lasting – constructed with extruded aluminum, a code approved epoxy photoluminescent insert, and a slip resistant aluminum or tread surface.

We recommend the following cleaning routine to maintain the appearance and performance of these stair nosings and treads.

1. Nosings and treads should be swept with a broom or vacuumed with a heavy-duty commercial vacuum cleaner at least once a week.

2. The entire nosing and tread should be periodically scrubbed with a stiff bristled brush using any commercial or industrial all purpose cleaner and thoroughly rinsed with clean water. We suggest the use of Murphy's Oil Soap®. A sponge mop should be used to remove excess water. We recommend two types of brushes, a stiff polypropylene hand brush or use of a stiff polypropylene drill chuck brush that can be installed into a battery operated drill (powered drill brush). The use of these brushes will help speed up the cleaning process and sufficiently scrub the slip resistant surface by lifting the accumulated dirt from between the gritted surface. Rinse with clean water and use the sponge mop to remove excess water. Let air dry.

To remove scuff and heel marks on the aluminum nosing or tread, rub with a fine steel wool and a commercial cleaning agent. Rinse with clean water and sponge mop excess water from the tread surface. Let air dry.

To remove heavy grease and oil from the nosings or treads, use Murphy's Oil Soap and brush vigorously with stiff bristled brush. Rinse with clean water and sponge mop excess water from the tread surface. Let air dry.

To remove snow and ice, use sodium chloride salt. Rinse with clean water and sponge mop excess water from the tread surface. Let air dry.

To remove chewing gum, first scrape away all excess gum. Use Murphy's Oil Soap and brush vigorously with stiff bristled brush. Rinse with clean water and sponge mop excess water from the tread surface. Let air dry.